



Wood / Stone



WN-911 American Oak

7.25" x 48"(184mm x 1219mm)



WN-912 Classic Oak

7.25" x 48"(184mm x 1219mm)



WN-913 Adan Oak

7.25" x 48"(184mm x 1219mm)



WN-914 Rustic Oak

7.25" x 48"(184mm x 1219mm)



WN-915 Mir Oak

7.25" x 48"(184mm x 1219mm)



WN-916 Modern Oak

7.25" x 48"(184mm x 1219mm)



WN-917 Retro Oak

7.25" x 48"(184mm x 1219mm)



WN-918 Enigmatic Oak

7.25" x 48"(184mm x 1219mm)



WN-919 Burian Oak

7.25" x 48"(184mm x 1219mm)



WN-920 Vail Oak

7.25" x 48"(184mm x 1219mm)



WN-921 Noel Oak

7.25" x 48" (184mm x 1219mm)



WN-922 White Oak

7.25" x 48" (184mm x 1219mm)



WN-923 Canberra Oak

7.25" x 48" (184mm x 1219mm)



WN-924 Smoked Oak

7.25" x 48" (184mm x 1219mm)



WN-925 Smoked Oak

7.25" x 48" (184mm x 1219mm)



WN-926 Nordic Oak

7.25" x 48" (184mm x 1219mm)



WN-801 Crystal Shale
18" x 24"(457mm x 609mm)



WN-802 Clouds Shale
18" x 24"(457mm x 609mm)



WN-803 Cosmic Sandstone
18" x 24"(457mm x 609mm)



WN-804 Eternal Slate
18" x 24"(457mm x 609mm)



WN-805 Elegence Sandstone
18" x 24"(457mm x 609mm)



WN-806 Minerva Limestone
18" x 24"(457mm x 609mm)



3mm



0.3mm

Al₂O₃ coating



WN-807 Raw Limestone
18" x 24"(457mm x 609mm)



WN-808 Royal Limestone
18" x 24"(457mm x 609mm)



WN-809 Pure Limestone
18" x 24"(457mm x 609mm)



WN-810 Horizon Limestone
18" x 24"(457mm x 609mm)



Non-abrasive



Resistant to stains



Hygienic and easily
maintained



Impact resistant



Light fastness: Grade
6 as per EN 20105



Resistant to
household chemicals



Resistant to burning



Healthy and
ecologically

Series	Size	Coating	Packing
Wood	7.25"x48"(184mmx1219mm)	Al ₂ O ₃	15pcs/carton
Stone	18"x24"(457mmx609mm)	Al ₂ O ₃	12pcs/carton
Test Item		Test method	Test report
Migration of certain elements	重金屬含量測試	EN 71 Part 3	PASS
Castor Chair Resistance	耐腳輪測試	EN ISO 4918	PASS
Edge straightness	直角度測試	EN ISO 24342	0.02mm~0.07mm
Side length	直線度測試	EN ISO 24342	0.03mm~0.10mm
Overall thickness	整體厚度測試	EN ISO 24346	±0.10mm
Thickness of layers	耐磨層厚度測試	EN ISO 24340	±0.02mm
Mass per unit area	單位面積重量測試	EN ISO 23997	3550g/m ²
Residual Indentation	殘餘壓痕測試	EN ISO 24343	0.04mm
Dimensional Stability	尺寸穩定性	ISO 23999	0.08%
Curling	翹曲度測試	ISO 23999	0.05mm
Flexibility and deflection	柔韌性測試	EN ISO 24344	PASS
Fire Rating	防焰阻燃測試	EN 13501-1	B ₁ -s1
Slip Resistance	防滑性能測試	EN 13893 / EN 14041	Level DS
Colour Fastness To Light	色牢度測試	ISO 105-B02	Above Grade 6
Formaldehyde Release	甲醛含量測試	EN 14041 / EN 717-1	E1
Burning cigarettes	香菸燒灼測試	EN 1399	Level 2
Essential characteristics(PCP)	五氯苯酚含量測試	EN 14041 / EN 12673	PASS
Thermal Conductivity	導熱測試	EN 12667	0.121W/(m·K)
Thermal Resistance	耐熱測試	EN 12667	0.041(m ² ·K)/W
Reach SVHC	危險物質釋放量測試	GZTC CHEM-TOP-092	PASS
Phthalates	鄰苯二甲酸鹽	EN 14372	PASS
French VOC Regulation	揮發性有機化合物	ISO 16000 parts -3,-6,-9,-11	A+
Classification	性能等級分類	EN ISO 10874	23,31

